


Declaration of performance

DoP No: 2005.04_EN



Manually operated swing gates

Identification code	Euro - Euro 2 - Europa - Swing S - Proteus 2		
Serial number	xxxxxxxxxxxxxxxx example: DPHER12200		
Intended use	Swing gates are designed for controlled access to the premises, buildings or locations		
Contact address manufacturer	Heras B.V. - Hekdam 1 - 5688JE Oirschot - Netherlands		
System of assessment and verification of constancy of performance	System 3		
Harmonised standard	EN 13241-1:2003+A2:2016		
Identification number notified body	0620 Kiwa		
Report number	140602166, 048-14		
Declared performance	Essential characteristics	Performance	Requirements
	Watertightness	NPD	4.4.1
	Release of dangerous substances	NPD	4.2.9
	Resistance to wind load	class 2	4.4.3
	Thermal resistance (where relevant)	NPD	4.4.5
	Air permeability	NPD	4.4.6
	Safe opening (for vertically moving doors)	NPD	4.2.8
	Definition of geometry of glass components	NPD	4.2.5
	Mechanical resistance and stability	PASS	4.2.3
	Operating forces (for power operated doors)	NPD	4.3.3
Durability of watertightness, thermal resistance and air permeability against degradation	NPD	4.4.7	
Signed by			
Name	Gilles Rabot		
Position	Director		
Place	Oirschot		
Date	20-02-2020		
Signature			

Declaration of performance

DoP No: 2005.04_EN



Manually operated swing gates

Assessed products	Euro - Euro 2 – Europa - Swing S*
	<p>Type: Heracles, Atlas, Olympus, Orpheus, Athos, Pegasus, Pallas</p> <p>Version: single, double</p> <p>Drive: -</p> <p>Control unit: -</p> <p>Opening single: $1\text{m} \leq 5\text{m}$</p> <p>Height: $\leq 2,5\text{m}, \leq 2\text{m}^*$</p> <p>Proteus 2</p> <p>Type: Pallas 868 + Uni</p> <p>Version: single, double</p> <p>Drive: -</p> <p>Control unit: -</p> <p>Opening single: $1\text{m} \leq 2\text{m}$</p> <p>Height: $\leq 2\text{m}$</p>