

Certificate of Product Approval

Certificate Number: 1454i Issue: 02

Heras Perimeter Protection Ltd

Carr Hill Industrial Estate Balby Doncaster DN48WA

Product

Zenith B201 A1

security gates

Standard

LPS 1175: Issue 8

Requirements and testing procedures for the LPCB certification and listing of intruder resistant building components, strongpoints, security enclosures and free-standing barriers

This certificate and appendix is maintained and held in force through regular surveillance activities





Chris Hunt

27 September 2021

27 September 2021

Date of Issue

Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.







Appendix to Certificate No: 1454i Heras Perimeter Protection Ltd

Issue: 02

Security Gates

Product Name	Туре	Minimum Height (m)	Maximum Height (m)	Minimum Width (m)	Maximum Width (m)	Security Rating	LPCB ref. No.
Zenith B201 A1	Single leaf inward/outward opening gate	1.8	4.2	1.2	2.0	A1 (SR1)	1454i/01
	Double leaf inward/outward opening gate	1.8	4.2	2.0	10.0		

Compatible Locking Configurations

Product Name	Туре	Compatible Locking Systems	
		Active	Passive
Zenith B201 A1	Single leaf inward/outward opening gate	1	N/A
	Double leaf inward/outward opening gate	1	2

Compatible Locking Devices

Compatible	Manufacturer	Model	Туре	Compatible Opera	Compatible	
Locking Device				External	Internal	Padlocks
1	Heras Perimeter Protection Ltd	Padlockable slide latch	Sliding bar	Padlock and sliding bar	-	A, B and C
2	Heras Perimeter Protection Ltd	Drop-bolt	Drop bolt	-	Drop bolt	-

Compatible Padlocks

Padlock Reference	Manufacturer	Model	Туре
А	Abloy	PL330	Refer to LPCB certificate 1245a
В	Abloy	PL350	Refer to LPCB certificate 1245a
С	Squire	SS65s	Refer to LPCB certificate 1179a

Notes:

- 1. The single leaf gates above 2.4 m high incorporate a lintel panel above them.
- 2. The drop bolt (s) do not need to be engaged in order to achieve the security rating noted.
- 3. The gates shall be mounted onto flat topography and are available in configurations to suit either surface mounting onto hard surfaces or embedding within concrete foundations placed in the ground. Furthermore, the local ground onto/into which the gate is installed shall offer compatible strength.
- 4. The gap between the bottom of the gate leaf and the ground must not exceed 50 mm.

This certificate and appendix is maintained and held in force through regular surveillance activities

ce by Signed for BRE Global Ltd.

Chris Hunt Verifier

27 September 2021

27 September 2021

Date of Issue Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



